

Product Data Sheet

BYCOTEST
Non-Destructive Testing

Fluorescent penetrant **BYCOTEST FP42**



General Description

- Medium sensitive fluorescent penetrant
- Water washable and solvent removable
- Sensitivity level 2 according to AMS 2644 (MIL-I-25135)
- Non-corrosive according to ASME B&PV Code and EN-ISO 3452-2
- Meets the requirements of most of the international norms for penetrants

Specification

Sulphur (ppm)	Max 200
Halogen (ppm)	Max 200

Typical properties

Density (g/ml)	ca 0,86
Flash point (°C)	ca 100
Colour (in black light)	fluorescent yellow-green

Order code

10-5118	400 ml aerosol (12 aerosols/box)
10-5115	5 L plastic can

Other information

Method of use: see separate Data Sheet
Composition and handling: see Safety Data Sheet

Safety and First Aid

Read the Bycotest Safety Data Sheet(s) for safety information before using the product(s).

The information contained in this document is provided free of charge and is based on technical data that we believe to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. We accept no liability for any loss, damage or expense arising from, or in connection with, the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent, nor as a recommendation to infringe any patent.

Certificates, Safety and Product Data Sheets are available at www.bycotest.com.

Bycotest AB Box 530 SE 651 12 KARLSTAD Sweden Phone: +46 (0)54 29 39 50 Fax: +46 (0)54 85 05 58 www.bycotest.com info@bycotest.com

Issue June 2009