


# Product Data Sheet

**BYCOTEST**  
— Non-Destructive Testing —

## Fluorescent penetrant **BYCOTEST FP400**



### General Description

- High-sensitive fluorescent penetrant
- Biodegradable, based on easily degradable surfactants
- Sensitivity level 3 according to AMS 2644 (MIL-I-25135)
- Non-corrosive according to ASME B&PV Code and EN-ISO 3452-2
- Meets the requirements of most of the international norms for penetrants
- Water washable and solvent removable
- Free from petroleum based solvents
- High flash point

### Specification

Sulphur (ppm)	Max 200
Halogen (ppm)	Max 200

### Typical properties

Density (g/ml)	ca 0,96
Flash point (°C)	>100

### Order code

10-5135	5 L plastic can
---------	-----------------

### Other information

Method of use: see separate Data Sheet  
Composition and handling: see Safety Data Sheet

### Safety and First Aid

Read the Bycotest Safety Data Sheet(s) for safety information before using the product(s).

The information contained in this document is provided free of charge and is based on technical data that we believe to be reliable. It is intended for use by persons having technical skill and at their own discretion and risk. We accept no liability for any loss, damage or expense arising from, or in connection with, the use of the information. Furthermore, none of the contents of this publication should be taken as a licence to operate under any patent, nor as a recommendation to infringe any patent.

Certificates, Safety and Product Data Sheets are available at [www.bycotest.com](http://www.bycotest.com).

Bycotest AB Box 530 SE 651 12 KARLSTAD Sweden Phone: +46 (0)54 29 39 50 Fax: +46 (0)54 85 05 58 [www.bycotest.com](http://www.bycotest.com) [info@bycotest.com](mailto:info@bycotest.com)

Issue Oct 2009